

PRODUCT DATA SHEET





# **DESIGN: DIETIKER, 2003**

The Eco table is driven by pure simplicity and high quality. Eco is available in HPL, veneer and linoleum on request. It comes with optional cable management system.

ECO TABLE SQUARE Ref. No. 3"	31021
------------------------------	-------

		_
		71
Ε		
5 cm		
75		
	lU	U

В			
	-	L	_

DIMENSIONS				
Length L cm	70	80	90	100
Width B cm	70	80	90	100
Table top thickness 22 mm				
Number of chairs	2	4	4	4

## **HPL ACCORDING TO STANDARD COLLECTION**

Edge ABS

Edge 15

# **VENEER**

Edge U5

Linoleum

ECO TABLE RECTANGLE	Ref. No. 31022





DIMENSIONS									
Length L cm	90	120	120	140	160	120	160	180	200
Width B cm	70	90	70	70	70	80	80	80	100
Table top thickness 22 mm									
Number of chairs	4	4	4	6	6	4	6	8	8

### **HPL ACCORDING TO STANDARD COLLECTION**

Edge ABS

Edge 15

# **VENEER**

Edge U5

Linoleum

# TECHNICAL DATA

### CONSTRUCTION

4-leg apron table construction with separate table top.

Rectangular steel tube yoke-shaped frame 30/30/2 mm, welded on mitre joint.

Cross member, rectangular steel tube 30/30/2 mm,

apron rails and cross members are welded together.

Table top screwed from underneath through cross members using countersunk screws, 3 mm gap between table top and apron.

### **TABLE TOP**

Base panel SPAN E1 22 mm, optionally with synthetic resin, linoleum or veneer finish.

### STEEL PARTS SURFACE TREATMENT

Powder-coated, aluminium light

### WOOD SURFACE TREATMENT

Stained with highly light-fast, water-based stain (dye/pigment) on request.

Colours according to the Dietiker standard stain collection/Arik Levy stain collection colour chart or customer colour sample.

Coated with 2-component, water-based polyurethane lacquer that has excellent light-fast properties and acts as a UV filter.


Meets highest standards according to DIN 68861 and complies with increased fire safety requirements (flame-retardant).

The same applies to solvent-based coatings.

### **GLIDES**

Adjustable glides

### **ACCESSORIES**



Cable management (on request)